HSF Pb RoHS









PCB LAYOUT

SPECIFICATION

Current Rating:	1.5Amp
Insulation Resistance:	1000M ohms min
Contact Resistance:	20M ohms max
Dielectric Withstanding:	AC500V
Operating Temperature:	-65°C to +125°C
Contact Material:	Brass
Insulator Material:	PA6T UL 94V-0 Black

Ordering Code:

FHDU07 - X - X - D - X - X - X - X

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

① Series No:

② No.of Contacts
02 To 80

③ Contact Plating:
G0:Gold flash S0:Selective
G1:3U" Gold S1:Selective 3u"
G2:5u" Gold S2:Selective 5u"
G3:10u "Gold S3:Selective 10u"
G4:15u" Gold S4:Selective 15u"
G5:30u" Gold S5:Selective 30u"
SN:Tin

④ Connector Type
D:Dual

⑤ Plastic High:
H:4.6
Please mark the desired length in the H

⑥ Insulator Material
B:PA6T
C:LCP
D:PA46
E:PA9T

⑦ Packing
A:Tray
B:Bag
T:Tube
U:Tube+CAP
R:Tape&Reel
W:Tape&Reel+CAP

⑧ Special Function
A:Type A
B:Type B

REV	DESCRIPTION	DATE

Unless Otherwise specified tolerance
X. ±0.35 X.XX: ±0.20
X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown	UNIT: mm
DRAW YG ZHONG	DATE 01/05/2016
CHECK BobYang	DATE 01/05/2016

3rd ANGLE PROJECTION

ANTENK ELECTRONICS CO,.LTD
Http://www.antenk.com
E-mail:sales@antenk.com

TITLE: 2.00mm Female Header Dual Row Straight Type

DRAWING NO: FHDU07-XXDXXXX

PRODUCT NO: FHDU07-XXDXXXX

Antenk