




HSF






ROHS



Right angle pin connector solder tail,
single row
Availability from:2 to 40 contacts
Standard number of contacts 40

A:Type1



Right angle pin connector solder tail,
double row
Availability from:4 to 80 contacts
Standard number of contacts 80

B:Type2

SPECIFICATIONS:

Insulator: PPS
Flammability: UL 94V-0
Sleeve: Brass
Contact clip(3 finger): Beryllium copper
Mating pin ϕ : 0.38 to 0.50 mm
Forces: (polished steel gauge ϕ 0.41mm)
-Insertion 0.5 N typ.
-Withdrawal 0.2 N typ.
Mechanical life: min 500 cycles
Rated current: 1A
Contact resistance: max 10 m Ω
Dielectric strength: min 500V RMS

Ordering Code:

MPHDR - X - X - X - X - 00
① ② ③ ④ ⑤ ⑥

- ① MPHDR series
- ② Contact NO:
XX=XXpin
For example:
06=06pin
- ③ Pin Plated
0; No
1; Tin 150 μ "
2; Tin 200 μ "
3; G/F
4; Gold 3 μ "
5; Gold 10 μ "
6; Gold 15 μ "
S; Special
- ④ Packing
A:Tray B:Bag
C:Tube D:Tape Reel
- ⑤ Type selection
A:Type1 B:Type2
- ⑥ Series number
00

Unless Otherwise specified tolerance
X $\pm$ 0.35 X.XX $\pm$ 0.20
X.X $\pm$ 0.25 X.XXX $\pm$ 0.15

SCALE: As Shown UNIT: mm
DRAW Gong Feng DATE 09/11/2017
CHECK BobYang DATE 09/11/2017



Antenk® ANTENK ELECTRONICS CO.,LTD
Http://www.antenk.com
E-mail:sales@antenk.com

TITLE: Machined Socket connectors 2.00 mm:
MPHDR series

DRAWING NO: MPHDR-XXXXXX00

PRODUCT NO: MPHDR-XXXXXX00

REV	DESCRIPTION	DATE
1		